

Quick Installation Guide for Elite-300-EP23:

Step 1: Mounting the Device

Place the device securely under the dashboard or in another discreet location.

Ensure the device is positioned on a flat surface and will not move during vehicle operation.

Avoid:

Attaching to wiring looms or harnesses.

Placing near sources of electrical noise (e.g., engine systems, ignition coils).

Step 2: GPS/GSM Antenna Installation

The antenna has two separate wires:

- 4G Wire (for GSM): Connect this wire to the GSM port on the device.
- GNSS Wire (for GPS): Connect this wire to the GPS port on the device.

Ensure the antenna has a clear, unobstructed view of the sky in all directions.

Mount the antenna on a horizontal surface (minimum 10cm x 10cm) for optimal GPS reception.

Place high up in the dashboard, discreetly mounted on plastic surfaces where possible for GSM reception.

Important:

Do NOT mount the antenna on Metal surfaces for GPS.

Do NOT place near electrical noise sources (e.g., engine systems, ignition coils, leads).

Maintain at least 50cm clearance from other antennas.




Step 3: Power Harness and Serial Port Connections

For power harness I/O and optional serial port connectors, refer to the IntelliTrac wiring guide or contact IntelliTrac for additional wiring information, including external inputs.

Red: Battery (12-24 VDC, fused). **White:** Ignition (12-24 VDC).

Black: Ground.

Basic 3 Wire Connections	
Red	Battery 12-24 VDC (fused)
White	Ignition 12-24 VDC
Black	Ground



Step 4: Check For LED indicators:

- Device is running.
 2sec
- GPS locked. ●● 2sec ●●
- Device registered to network.
- Device connected to server. ●● 2sec ●●

BEFORE LEAVING VEHICLE

Confirm installation and activate device by calling IntelliTrac on Installer Hotline (03) 8456 0681

A service representative will confirm the device is operating correctly and calibrate odometer/hourmeter

